

Sound Level Meter

Portable digital sound level meter 8925/ 8928



8925

- ▲ THE MOST COST-EFFECTIVE BEST SELL METER
- ▲ FEATURES W/DIGITAL DISPLAY AND ANALOG BAR GRAPH
- ▲ POCKET SIZE FASHION & RIGID DESIGN
- ▲ AUTO / MANUAL RANGING ,4 MEASUREMENT RANGES IN 10 STEPS
- ▲ MAX HOLD
- ▲ RECORD MAX / MIN
- ▲ FAST / SLOW RESPONSE IS SELECTABLE
- ▲ A / C WEIGHTING IS SELECTABLE
- ▲ EASY TO CALIBRATE BY STANDARD CALIBRATOR
- ▲ ANALOG OUTPUT
- ▲ TRIPOD MOUNTABLE



8928

| Model | 8925 | 8928 |
|-----------------------------|--|--|
| Measure range | A weight: 40dB~130dB C weight: 45dB~130dB | |
| Digital display (4 ranges) | 40~70dB, 60~90dB, 80dB~110dB, 100dB~130dB. | |
| Digital display resolution | 0.1dB | |
| Digital updating time | 160mS | |
| Quasi-analog bar (4 ranges) | 40~70dB, 60~90dB, 80dB~110dB, 100dB~130dB. | |
| Quasi-analog bar resolution | 1dB | |
| Bar updating time | 40mS | |
| Accuracy at 94dB, 1KHz | +/-2dB | |
| Analog output | AC 0.707Vrms(FS) | |
| Microphone | Dia.6mm electric condenser microphone | Dia.10mm electric condenser microphone |
| Frequency range | 31.5Hz~8KHz | |
| Battery life time | 60 hours typical | 30 hours typical |
| Windscreen | YES | N/A |
| LCD size (mm) | 30(H)x35(W) | 32(H)x42(W) |
| Operating temp. | 0~50°C | |
| Operating RH% | Humidity < 80% | |
| Storage temp. | -20~50°C | |
| Storage RH% | Humidity < 90% | |
| Dimension(mm) | 57x230x44 | 72x182x30 |
| Weight | ~130g | ~150g |
| Battery | AAA x 4pcs | 9V x 1pc |
| Standard Package | Meter/Battery/Manual/Paper box | |
| Optional Accessory | N/A | PU pouch |

Optional



POUCH (SOFT CARRYING CASE)
P/N: VM68926U
FOR 8928
COLOR: BLACK
SIZE:176x75x35mm