THIS DOCUMENT CONTAINS PROPRIETARY DATA OF POLARIS INDUSTRIAL ENTERPRISES,INC. NO DISCLOSURE, REPRODUCTION, OR USE OF ANY PART THERE OF MAY BE MADE EXCEPT BY WRITTEN PERMISSION.

REV.	BY	DATE	APPRVL.	P/N RV4NAYSJ

SPECIFICATIONS

RESISTANCE RANGE ---------- 1K,5K,10K
RESISTANCE TOLERANCE ---------- ±10%
POWER RATING ----------2 WATTS @70°C
DERATED TO 0 WATTS AT 120°C
MECHANICAL ANGLE ---------- 314°
OPERATING VOLTAGE ---------- 500V SUBJECT TO POWER RATING
INSULATION RESISTANCE ---------- DRY: 10K MEG OHM
WET: 100K MEG OHM
DIELECTRIC STRENGTH ---------- 900 V RMS AT SEA LEVEL
OPERATING TORQUE ---------- 1 OZ/IN TO 6 OZ/IN
OPERATING TEMPERATURE ---------- -65°C TO +125°C
ROTATIONAL LIFE ---------- 25,000 CYCLES



MATERIALS

HOUSING ---------- STAINLESS STEEL
TERMINALS ---------- GOLD PLATED
SHAFT ---------- STAINLESS STEEL
RESISTIVE ELEMENT ---------- HOT MOLDED CARBON

ENVIRONMENTAL

RESISTANCE TO SOLDERING HEAT ------- 350°C FOR 5 SECONDS
HUMIDITY RANGE ---------- PER MIL-R-94
VIBRATION RANGE ---------- PER MIL-R-94
SHOCK RESISTANCE ---------- PER MIL-R-94
LOAD LIFE ---------- 1000 Hr AT 70°C

OPTIONS

OTHER STANDARD RESISTANCE VALUES AVAILABLE
CUSTOM SHAFTS AND BUSHINGS
SPECIAL TAPERS
FOURTH (CENTER) TERMINAL
HIGH LIFE
ATTACHED SWITCH

SCHEMATIC



TOLERANCES
XX = +/- .010" FRACT. = +/- 1/64"
XXX= +/- .005" ANGLES = +/- 1/2°
ALL SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.

SCALE	DATE:	12-7-07
NONE	BY	AT
	APPRV'D	
CODE IDENT: 19477		

ETI SYSTEMS
CARLSBAD
CALIFORNIA

TITLE
SINGLE TURN
POTENTIOMETER

PART NO.
RV4NAYSJ

THIS DOCUMENT CONTAINS PROPRIETARY DATA OF POLARIS INDUSTRIAL ENTERPRISES,INC. NO DISCLOSURE, REPRODUCTION, OR USE OF ANY PART THERE OF MAY BE MADE EXCEPT BY WRITTEN PERMISSION.

REV.	BY	DATE	APPRVL.	P/N RV4NAYSD

SPECIFICATIONS

RESISTANCE RANGE ------ 100,500,1K,5K,10K,50K,100K,1MEG OHM
RESISTANCE TOLERANCE ---------- ±10%
POWER RATING ----------2 WATTS @70°C
DERATED TO 0 WATTS AT 120°C
MECHANICAL ANGLE ---------- 314°
OPERATING VOLTAGE ---------- 500V SUBJECT TO POWER RATING
INSULATION RESISTANCE ---------- DRY: 10K MEG OHM
WET: 100K MEG OHM
DIELECTRIC STRENGTH ---------- 900 V RMS AT SEA LEVEL
OPERATING TORQUE ---------- 1 OZ/IN TO 6 OZ/IN
OPERATING TEMPERATURE ---------- -65°C TO +125°C
ROTATIONAL LIFE ---------- 25,000 CYCLES





MATERIALS

HOUSING ---------- STAINLESS STEEL
TERMINALS ---------- GOLD PLATED
SHAFT ---------- STAINLESS STEEL
RESISTIVE ELEMENT ---------- HOT MOLDED CARBON

ENVIRONMENTAL

RESISTANCE TO SOLDERING HEAT ------ 350°C FOR 5 SECONDS
HUMIDITY RANGE ---------- PER MIL-R-94
VIBRATION RANGE ---------- PER MIL-R-94
SHOCK RESISTANCE ---------- PER MIL-R-94
LOAD LIFE ---------- 1000 Hr AT 70°C

OPTIONS

OTHER STANDARD RESISTANCE VALUES AVAILABLE
CUSTOM SHAFTS AND BUSHINGS
SPECIAL TAPERS
FOURTH (CENTER) TERMINAL
HIGH LIFE
ATTACHED SWITCH

SCHEMATIC



TOLERANCES	SCALE	DATE: 12-7-07		TITLE	PART NO.
XX = +/- .010" FRACT. = +/- 1/64" XXX= +/- .005" ANGLES = +/- 1/2° ALL SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.	NONE	BY AT APPRV'D	ETI SYSTEMS CARLSBAD CALIFORNIA	SINGLE TURN POTENTIOMETER	RV4NAYSD
	CODE IDENT: 19477				

THIS DOCUMENT CONTAINS PROPRIETARY DATA OF POLARIS INDUSTRIAL ENTERPRISES,INC. NO DISCLOSURE, REPRODUCTION, OR USE OF ANY PART THERE OF MAY BE MADE EXCEPT BY WRITTEN PERMISSION.

REV.	BY	DATE	APPRVL.	P/N RV4LAYSA

SPECIFICATIONS

RESISTANCE RANGE ---------- 5K,10K,50K OHM
RESISTANCE TOLERANCE ---------- ±10%
POWER RATING ----------2 WATTS @70°C
DERATED TO 0 WATTS AT 120°C
MECHANICAL ANGLE ---------- 314°
OPERATING VOLTAGE ---------- 500V SUBJECT TO POWER RATING
INSULATION RESISTANCE ---------- DRY: 10K MEG OHM
WET: 100K MEG OHM
DIELECTRIC STRENGTH ---------- 900 V RMS AT SEA LEVEL
OPERATING TORQUE ---------- 1 OZ/IN TO 6 OZ/IN
OPERATING TEMPERATURE ---------- -65°C TO +125°C
ROTATIONAL LIFE ---------- 25,000 CYCLES



MATERIALS

HOUSING ---------- STAINLESS STEEL
TERMINALS ---------- GOLD PLATED
SHAFT ---------- STAINLESS STEEL
RESISTIVE ELEMENT ---------- HOT MOLDED CARBON

ENVIRONMENTAL

RESISTANCE TO SOLDERING HEAT ------- 350°C FOR 5 SECONDS
HUMIDITY RANGE ---------- PER MIL-R-94
VIBRATION RANGE ---------- PER MIL-R-94
SHOCK RESISTANCE ---------- PER MIL-R-94
LOAD LIFE ---------- 1000 Hr AT 70°C

OPTIONS

OTHER STANDARD RESISTANCE VALUES AVAILABLE
CUSTOM SHAFTS AND BUSHINGS
SPECIAL TAPERS
FOURTH (CENTER) TERMINAL
HIGH LIFE
ATTACHED SWITCH

SCHEMATIC



TOLERANCES	SCALE	DATE: 12-7-07	ETI SYSTEMS CARLSBAD CALIFORNIA	TITLE	PART NO.
XX = +/- .010" FRACT. = +/- 1/64" XXX= +/- .005" ANGLES = +/- 1/2° ALL SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.	NONE	BY AT		SINGLE TURN POTENTIOMETER	RV4LAYSA
		APPRV'D			
	CODE IDENT: 19477				